

CESAB PRODUCT RANGE

Counterbalanced and Warehouse Equipment





WAREHOUSE EQUIPMENT

Hand pallet trucks





CE200 - 230 - 300

-  2.0 t - 2.3 t - 3.0 t
-  The 2.3 t model is also available with low forks, quicklift feature and handbrake. Low forks are standard on the 2.0 t model.






CE200ST

-  2.0 t
-  Stainless steel version.






H210 - 210E

-  1.0 t
-  800 mm
-  Manual and electric scissor lifters.

Powered pallet trucks






P113

-  1.3 t
-  24V / 63 Ah
-  Integrated batteries and charger.






P214 - 216 - 218 - 220 - 225

-  1.4 t - 1.6 t - 1.8 t - 2.0 t - 2.5 t
-  24V / 300 Ah
-  Optional operator platform available for P220.







P320 - 322

-  2.0 t - 2.2 t
-  24V / 600 Ah
-  Available with a choice of travel speed (6, 8, 10 km/h).

Reach trucks







R112 - 114 - 116

-  1.2 t - 1.4 t - 1.6 t
-  8500 mm
-  48V / 620 Ah
-  Also available as a drive-in version with narrow overhead guard.







R212 - 214 - 216

-  1.2 t - 1.4 t - 1.6 t
-  8500 mm
-  48V / 620 Ah
-  Also available as a cold store version as well as drive-in version with narrow overhead guard.







R314 - 316 - 318 - 320 - 325

-  1.4 t - 1.6 t - 1.8 t - 2.0 t - 2.5 t
-  13000 mm
-  48V / 930 Ah
-  Also available as a cold store version, with or without heated cabin, as well as a drive-in version with narrow overhead guard.

Powered stacker trucks







S110 - 110S

-  1.0 t
-  2000 mm
-  24V / 63 Ah
-  Integrated batteries and charger. S110S: straddle support arm variant.







S210 - 212 - 214

-  1.0 t - 1.2 t - 1.4 t
-  4755 mm
-  24V / 300 Ah
-  Optional operator platform available.







S215 - 216 - 220

-  1.45 t - 1.6 t - 2.0 t
-  5400 mm
-  24V / 500 Ah
-  Available with a choice of chassis width.







S208L

-  0.8 t
-  1580 mm
-  24V / 230 Ah
-  Can lift up to 2000 kg when lifting with the support arms only. Available with optional automatic height adjustment.







S212L - 214L

-  1.2 t - 1.4 t
-  4755 mm
-  24V / 300 Ah
-  Elevating support arms. Optional operator platform available.







S215L - 216L - 220L

-  1.45 t - 1.6 t - 2.0 t
-  5400 mm
-  24V / 500 Ah
-  Elevating support arms.



S220D

-  1.0 t
-  2100 mm
-  24V / 300 Ah
-  Double stacker, lifts 800 + 1200 kg lifting with forks + support arms or 2000 kg when lifting with the support arms only. Optional operator platform available.



S212S

-  1.2 t
-  4755 mm
-  24V / 300 Ah
-  Straddle support arms. Optional operator platform also available.







S214S

-  1.4 t
-  5350 mm
-  24V / 500 Ah
-  Straddle support arms.







S312 - 314 - 316 - 320

-  1.2 t - 1.4 t - 1.6 t - 2.0 t
-  6000 mm
-  24V / 500 Ah
-  Available with a choice of speeds up to 10km/h.



S312L - 314L - 316L - 320L

-  1.2 t - 1.4 t - 1.6 t - 2.0 t
-  6000 mm
-  24V / 500 Ah
-  Elevating support arms. Available with a choice of speed, up to 10km/h.



S314S




-  1.4 t
-  5350 mm
-  24V / 500 Ah
-  Straddle support arms.

COUNTERBALANCED

3-wheel electric trucks






B210 - 213 - 215

 1.0t-1.25t-1.5t
 6470 mm
 24V / 1000 Ah






B315 - 316 - 316L - 318 - 318L - 320

 1.5t-1.6t-1.8t-2.0t
 7470 mm
 48V / 750 Ah

4-wheel electric trucks






B415 - 416 - 416L - 418 - 418L - 420

 1.5t-1.6t-1.8t-2.0t
 7470 mm
 48V / 750 Ah






B620 - 625 - 625L - 630 - 630L - 635

 2.0t-2.5t-3.0t-3.5t
 6500 mm
 80V / 775 Ah






B640 - 645 - 650

 4.0t-4.5t-5.0t
 6500 mm
 80V / 930 Ah

Compact electric trucks






cenTAURO 48 160L - 200L

 1.6t-2.0t
 6970 mm
 48V / 840 Ah






cenTAURO 80 250 - 300

 2.5t-3.0t
 6860 mm
 80V / 735 Ah

Heavy duty electric truck



B860 - 870 - 885

 6.0t-7.0t-8.5t
 6450 mm
 80V / 1250 Ah

COUNTERBALANCED

4-wheel engine trucks torque converter



M315 - 318

	1.5 t - 1.8 t
	6970 mm
	DIESEL / LPG



M320 - 325

	2.0 t - 2.5 t
	6970 mm
	DIESEL / LPG



M330 - 335

	3.0 t - 3.5 t
	6970 mm
	DIESEL / LPG

4-wheel engine trucks hydrostatic



Drago 150 - 180 - 200

	1.5 t - 1.8 t - 2.0 t
	6170 mm
	DIESEL / LPG



Drago H 250 - 300 - 350

	2.5 t - 3.0 t - 3.5 t
	7960 mm
	LPG



Drago E 250 - 300 - 350

	2.5 t - 3.0 t - 3.5 t
	7960 mm
	LPG

Legend

	Rated capacity		Additional info
	Maximum lifting height		Fuel type
	Maximum battery capacity		Nominal draw-bar pull

The data in this specification sheet was determined based on our standard testing conditions. Operating performance may vary depending on the actual specification and condition of the truck as well as the condition of the operating area. Availability and specifications are determined regionally and are subject to change without notice. Please consult your authorised CESAB dealership for further details. RANGE_EN_2017 / P&B RANGE V54 — Copyright CESAB Material Handling E.Urope.

